



» The Essential POS Enabler »

Xtreme Turbo V2

15" POS Touch Terminal

- Brings Power into POS Design and Efficiency.
- Powerful Intel® Processor for your POS software and applications.
- Bezel free 15" TFT-LCD, LED backlight, Projected Capacitive Touch (Multi Touch).
- DDR3L memory supports up to 16GB
- Storage SSD (Default) / mSATA or HDD (Optional)
- Flexible modular design and optional customer display.
- Convenient compact POS and 45° tilt angle.



Printer Stand (optional)

Customer Display:



1 2nd Display - VFD 2x20



2 2nd Display - 9.7" 1024 x 768



3 2nd Display - 15" 1024 x 768

Interface:

- 1 * VGA
- 3 * USB 2.0, 2 * USB 3.0
- 2 * Serial (RS-232) Ports
- 1 * RJ45 1000M LAN
- 1 * Line out, 1 x Mic
- 1 * 12V DC IN

SSD Mountable from the outside



Applications:



Supermarket



Malls & Entertainment



Merchant Establishment



Hospitals / Pharmacy



Banks



Restaurants



Hotels



School / Education Institution



» The Essential POS Enabler »

Xtreme Turbo V2

15" POS Touch Terminal



E-PoS XTREME Series

| ITEM: | Xtreme Turbo V2: E-POS-XTV2-J1900 |
|---|--|
| CPU: | Intel® Celeron J1900 2.0GHz Quad-core 10W |
| Memory: | 4GB DDR3L 1333/1600MHz Optional up to 8GB (Standard 4 GB RAM) |
| Storage: | Storage SSD (Default) / mSATA or HDD (Optional) |
| Graphics: | Intel® HD Graphics |
| Display: | 15" Active TFT color LCD, resolution 1024 x 768, , brightness 350cd/m ² , LED backlight |
| Viewing Angle: | 45° adjustable |
| Touch Screen: | Capacitive Touch Panel |
| Audio: | ALC 662 6 channels, MIC and Line-out |
| LAN: | Realtek RTL8111H 1000M |
| Expansion Slot: | 1 * Mini PCIE(WIFI, 4G module), 1 x EXP PCIE |
| Optional 2nd Display: | 9.7" 1024x768 / 15" 1024x768 |
| External I/O Interface: | 1 * VGA |
| | 1 * RJ45 1000M LAN |
| | 3 * USB 2.0, 2 * USB 3.0 |
| | 2 * Serial (RS-232) Ports |
| | 1 * RJ45 1000M LAN |
| | 1 * Line out, 1 x Mic |
| | 1 * DC +12V input power-jack |
| Optional OS: | Windows 7 (32 & 64) Windows 10 and Windows 10 IoT LTSB, Linux |
| Optional Peripherals: | 3-track MSR, RFID reader, Fingerprint, IC Card reader, i-Button, VFD Display 2X20 characters(COM) |
| Input Power: | 12V/2.5A power Adapter |
| Power Supply: | AC100~240V / 14 ~ 63Hz |
| Physical Dimensions: | 354(L)*181(W)*341(H)cm |
| Operating Temp: | -10 ~ 60°C, 0-95% humidity |



CARE . TRUST . RESPONSIBILITY



Download Our APP

Partner Tech Middle East Group

SALES OFFICE: Office No. 1004, 10th Floor, Aspect Tower, Happiness Street, Business Bay, Dubai, UAE
 TECHNICAL & WAREHOUSE: Plot S10119, Gate 7, South Zone, Jebel Ali, Dubai, UAE
 SALES: +971 4 447 4273 | TECHNICAL & WAREHOUSE: +971 4 886 2980
 SALES: info@partnertechme.com | TECHNICAL SUPPORT: support@partnertechme.com

Distribution Brands

